



Technical changes reserved.  
All WEBOMATIC machines comply with the valid  
European regulations according to CE, EMC, EAC.

## SuperMax-i

The classic beneath the WEBOMATIC single chamber machines gains not only technical improvements, but also a revival in terms of design and control. Designed after the WEBOMATIC CleanDesign®ed duoMAT-series, the SuperMax-i adaptes an IGT-control. The IGT-*standard* is equipped with two language sets, regulates the sealing and cutting times and can be supplied with up to 10 programs. The sealing bars are easy to extract by hand – like in the duoMAT-series without any tools needed.

Sales launch from 1.8.2015

### Technical Data

<b>Machine size</b>	780 x 760 x 962 mm (W x D x H)
<b>Chamber size</b>	720 x 520 x 190 mm (W x D x H)
<b>Length of sealing bars, crosswise</b>	2 x 510 mm
<b>Usable chamber width</b>	600 mm
<b>Cycle performance</b>	2-3 cycles/min. depending on product size and required vacuum
<b>Control system</b>	IGT- <i>standard</i> ; monochrome TFT- screen with graphical user interface
<b>Vacuum pump</b>	63 m <sup>3</sup> /h integrated (100 m <sup>3</sup> /h on request)
<b>Optional features</b>	Gas supply, Soft-Air, double seam sealing, special voltage, single phase for 63 m <sup>3</sup> /h pump, slanted insert



## WEBOMATIC®

Maschinenfabrik GmbH  
Hansastr. 119  
44866 Bochum/Germany

Telephone +49 (0) 2327-3099-0  
Telefax +49 (0) 2327-3099-29  
info@webomatic.de  
www.webomatic.de